

Product Information IES files, certifications and approvals available on request

Modern design, high output, surface mounted can downlight. Suitable for high to medium ceilings. Broad variety of power outputs, colour temperatures, beam angles and customisations for every architectural or residential application. Features dedicated remotely located control gear suitable for all dimming protocols. Standard 5 year warranty.

Product Images More images and drawings available on request

LED Specification Citizen / Lumileds / Bridgelux alternatives available on request

BRAND	TYPE	LED CCT	LED CRI	DRIVE CURRENT	LED POWER	OUTPUT
CREE	CXA	2700K – 5000K	80 - 90	350 – 600mA	19.2W @ 600mA	109lm/W min

Luminaire Specification Customisations available on request

HEIGHT	TRIM	CUT OUT	MATERIAL	FINISH TYPE	MOUNTING	IP RATING
135mm	100mm diameter	Surface mounted	Machined Aluminium	Powder Coat	Surface	IP20

Product Code Generator example 2005.C3AM2.1

MODEL	SYSTEM POWER	LED CCT	LED CRI	BEAM ANGLE	FINISH	DIMMING	
2005. GENOA	A 14W	2 2700K	A 80	UN Ultra Narrow 15°	0. Silver	0 No dimming	
	B 20W	3 3000K	B 90	N Narrow 24°	1. White	1 Phase dimming	
	C 24W	4 4000K			M Medium 36°	2. Black	2 DALI dimming
		5 5000K			W Wide 60°	3. Custom	3 0-10V dimming

Ordering Information Please fill-up as per Product Code Generator

2005.						
-------	--	--	--	--	--	--