

**Product Information** IES files available on request

24V constant voltage LED flex for static white applications. Available in 5 CCT's of white 2700k – 6000k, and two ingress protections IP20 for dry locations, IP65 silicone jacket version for moist locations. Two different power levels (10w & 15w/m) allow for a broad range of uses for this highly versatile flexible LED strip. This strip makes use of a heavy rolled copper 3oz FPCB design with 50% increase in copper content over other strips, along with built-in IC technology to allow consistent light output over long runs.

Requires remotely located 24V power supply. Control gear available for DALI, Analogue 1-10v, DMX512, or Phase cut dimming protocols on request.

Standard 3 year replacement warranty.

**Product Images** More images and drawings available on request



PROFLEX 10



PROFLEX 15

**LED Specification** Power density alternatives available on request

BRAND	TYPE	LED CCT	LED CRI	VOLTAGE	LED POWER	OUTPUT
SAN'AN	2835 SMD	2700K – 6000K	90	24V DC	10W / 15W	90-110lm/W

**Strip Specification** Customisations available on request

IP RATING	HEIGHT	WIDTH	LENGTH	Material	MOUNTING
IP20 10W	1.6mm	10mm	50-15000mm	Rolled copper FPCB	Double sided adhesive
IP20 15W	1.6mm	10mm	25-10000mm	Rolled copper FPCB	Double sided adhesive
IP65 10W	4.5mm	14mm	60-15010mm	Silicone IP65 jacket	Double sided adhesive + silicone mounting brackets
IP65 15W	4.5mm	14mm	35-10010mm	Silicone IP65 jacket	Double sided adhesive + silicone mounting brackets

**Product Code Generator** example PRF-15-930K-20

MODEL	POWER PER/M	LED CRI	LED CCT	IP RATING
PRF- PROFLEX	10- 10W (120LED/m)	9 90CRI	27K- 2700K	20 IP20
	15- 15W (240LED/m)		30K- 3000K	
			40K- 4000K	
	50K- 5000K			

**Ordering Information** Please fill out as per Product Code Generator

PRF-				
------	--	--	--	--