

Product Information IES files, certifications and approvals available on request

Modern design, high output, surface mounted can downlight. Suitable for high to medium ceilings. Broad variety of power outputs, colour temperatures, beam angles and customisations for every architectural or residential application. Features integral control gear suitable for Trailing edge dimming, or for NON-DIM on/off applications. Standard 5 year warranty.

Product Images More images and drawings available on request



LED Specification Citizen / Lumileds / Bridgelux alternatives available on request

BRAND	TYPE	LED CCT	LED CRI	DRIVE CURRENT	LED POWER	OUTPUT
CREE	CXA	2700K – 5000K	80 - 90	250mA	8.8W	115lm/W Typ. CRI80

Luminaire Specification Customisations available on request

HEIGHT	WIDTH	CUT OUT	MATERIAL	FINISH TYPE	MOUNTING	IP RATING
110mm	72mm diameter	Surface mounted	Machined Aluminium	Powder Coat	Surface	IP20

Product Code Generator example 2010.A3AW1.1

MODEL	SYSTEM POWER	LED CCT	LED CRI	BEAM ANGLE	FINISH	DIMMING
2010. GENOA 10	A 10W	2 2700K	A 80	UN Ultra Narrow 15°	0. Silver	0 No dimming
		3 3000K	B 90	N Narrow 24°	1. White	1 Phase dimming
		4 4000K		M Medium 36°	2. Black	2 Remote DALI
		5 5000K		W Wide 45°	3. Custom	

Ordering Information Please fill-up as per Product Code Generator

2010.						
-------	--	--	--	--	--	--