

**Product Information** IES files available on request

24V constant voltage LED flex for static white applications. Available in 5 CCT's of white 2700k – 6000k, and two ingress protections IP20 for dry locations, IP65 silicone jacket version for moist locations. Three different power levels (9.6w/15w/19.2w/m) allow for a broad range of uses for this highly versatile flexible LED strip. Requires remotely located control gear, control gear available for DALI, Analogue 1-10v, DMX512, or Phase cut dimming protocols on request. Standard 3 year replacement warranty.

**Product Images** More images and drawings available on request



ECOFLEX 20



ECOFLEX 10

**LED Specification** OSRAM SMD alternatives available on request

BRAND	TYPE	LED CCT	LED CRI	VOLTAGE	LED POWER	OUTPUT
EPISTAR	2835 SMD	2700K – 6000K	80 - 90	24V DC	9.6W / 15W / 19.2W	120lm/W Typical

**Strip Specification** Customisations available on request

IP RATING	HEIGHT	WIDTH	LENGTH	Material	MOUNTING
IP20	1.6mm	8mm / 10mm	50-5000mm	Rolled copper FPCB	Double sided adhesive
IP65	4.5mm	10mm / 12mm	60-5010MM	Silicone IP65 jacket	Double sided adhesive + silicone mounting brackets

**Product Code Generator** example EF4-15-830K-20

MODEL	POWER PER/M	LED CRI	LED CCT	IP RATING
EF4- ECOFLEX	10- 9.6W (8mm)	8 80CRI	27K- 2700K	20 IP20
	15- 15W (10mm)	9 90CRI	30K- 3000K	65 IP65
	20- 19.2W (12mm)	40K- 4000K	50K- 5000K**	60K- 6000K

**Ordering Information** Please fill out as per Product Code Generator

EF4-				
------	--	--	--	--